



PO Box 1135/179 Belvedere Road, Keene, NH 03431
Sales Line: 1-800-394-5889 X 301 Tech Line: 1-603-355-4955 X 302

Instruction Sheet

**Part Number 727-22825HD A-727 Kickdown Band Strut, 1962
up**

Contents:

- 1-Billet Kickdown Strut
- 1-Instruction Sheet

Note: Before installation, read instructions carefully. If you do not understand any part of these instructions please call our tech line at the number listed above.

Safety Warning!!

Never operate this or any other 3 speed transmission without the proper safety devices in place. This includes both an SFI approved transmission safety shield and flexplate shield.

Any time you experience a universal joint or rear end failure you must disassemble the transmission and inspect the overrunning clutch assembly.

If you are unfamiliar with transmission repair and modifications, do not install this part. Instead, have it installed by a competent transmission technician who is familiar with such devices.

Failure to follow these directions and follow all safety procedures can result in serious injury or death!

Instructions:

Step 1:

Remove the transmission pan.

Step 2:

Loosen the band adjuster lock nut found on the driver's side of the case above the shift lever.

Step 3:

Remove the original band strut.

Step 4:

Install the new strut with the notched end toward the band and the flat side toward the oil pan.

Step 5:

Reinstall the pan and adjust the band to specifications.

Suggested Related Additional Components:

727-1399HP: A-727 Handbook

727-22825R: Kickdown Band, Red Solid W/O Oil Grooves

727-22825RS: Kickdown Band, Red Solid W/Oil Groove

727-22905LM: Front Servo, OEM Modified

727-22827M: Front Servo Cover, OEM Modified

727-22827-01: Front Servo Cover, Billet W/O Ring

